



Spotted Gum

Technical Specifications

» Grade & Surface

Standard & Better.

May contain, gum veins, gum pockets, insect trails, burls and borer holes that complement the natural characteristics of the plank visual. Surface texture options; Smooth or Light wire brush.

» Sizes

Classic Width Plank (4 Colours)

135 x 14.2 x 1820 mm inc. nested shorts.

Wide Plank (2 Colours)

180 x 14.2 x 1820 mm inc. nested shorts.

» Profile

Floating install. Patented Valinge 5g locking.

» Colour Range

135 mm, Classic width plank.

Blackbutt, Jarrah, Spotted Gum & Sydney Blue Gum.

180 mm, Wide plank.

Blackbutt & Spotted Gum.

» European Coating

Pre-finished, water based Robust UV Lacquer.

» Physical Properties

Formaldehyde Emissions, E1.

Reseller Enquiries

Adelaide

t +61 8 8268 8010
sa@preferencefloors.com.au

Brisbane

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne

t +61 3 9794 5111
vic@preferencefloors.com.au

Sydney


t +61 2 9738 1188
syd@preferencefloors.com.au

www.preferencefloors.com.au

PREFERENCE *Select* ENGINEERED TIMBER

AUSTRALIAN TIMBER RANGE





Key Features

- > Natural Australian Eucalyptus Species
- > Engineered construction to exacting standards
- > Impact resistant, durable and stable
- > Easy to install, minimal care & maintenance
- > Suitable for new construction or renovation projects
- > Stunning natural visuals providing warmth and character unique to our Australian timber
- > Australian warranty and customer service support

Sydney Blue Gum




Fast and easy install utilising the world renowned Valinge 5G locking profile.

Our Environment

The Preference Select Australian Species range is manufactured to provide class leading performance underpinned by third party eco-certification and accreditation.

This encompasses our raw material supply and all manufacturing processes. Our Australian timber is sourced from the sustained yield forestry operations certified under the Australian Forestry Standards Chain of Custody, (AS4707-2006). Only non-toxic materials are utilised throughout the entire production process.



Your Peace of Mind


With confidence you can specify or use Preference Select flooring knowing that it will not compromise our valuable environment and well-being. The range represents great value with fully supported Australian warranty provisions.

Blackbutt

Preference Select Engineered Timber, a natural choice

The unique colour and natural variation provided by Australian timber species make them an extremely versatile choice to enhance any interior décor.

Rich tones and varied grain patterns of the ever popular Spotted Gum, Sydney Blue Gum and Jarrah are supported by the natural straw palette of Blackbutt. The Australian Timber Range is further enhanced by unique surface treatments, and is pre-finished utilising the latest water based, non-toxic robust European coating technology. With the world renowned Valinge 5G locking profile Preference Select engineered planks are easy to install providing a no fuss, pre-finished, ready to walk on floor.



The Preference Select range is available in two widths: Classic Width 135 mm, and Wide Plank 180 mm.

Surface coating options include:

Semi-gloss or light wire brushed and Bona Matte for an ultra-modern look.

Jarrah

Species	Janka Rating	Thickness 14.2 mm	Width 135 mm	Width 180 mm	Square Edge Profile 5G Lock	Surface Flat Semi-Gloss	Surface Brushed Bona Matte
Blackbutt	9.1	✓	✓	✓	✓	135 mm	135 & 180 mm
Jarrah	8.5	✓	✓	N/A	✓	135 mm	N/A
Spotted Gum	11.0	✓	✓	✓	✓	135 mm	135 & 180 mm
Sydney Blue Gum	9.0	✓	✓	N/A	✓	135 mm	N/A

