

# African Wenge

TRANSFORM **DS**



100  

---

28160



190  

---

28890



530  

---

28282

# African Wenge



TRANSFORM **DS**

## TECHNICAL SPECIFICATIONS

|                 |                        |                           |                      |
|-----------------|------------------------|---------------------------|----------------------|
| Collection      | Transform DS           | M <sup>2</sup> per Box    | 3.62m <sup>2</sup>   |
| Type            | Vinyl Plank            | M <sup>2</sup> per Pallet | 202.72m <sup>2</sup> |
| Plank Thickness | 2.5mm                  | Surface                   | Saw Cut Emboss       |
| Dimensions      | 1320mm (L) x 196mm (W) | Profile                   | Micro Bevel          |
| Wear Layer      | 0.55mm                 | Protective Coating        | Protectonite®        |
| Planks per Box  | 14                     | Finish                    | Matte                |
| Colours         | 3                      | Installation Method       | Direct Stick         |

## PERFORMANCE SPECIFICATIONS

|                                  |   |                |
|----------------------------------|---|----------------|
| Abrasion Rating                  | Group T   | EN 660-2       |
| Classification                   | 23, 33, 42  | EN ISO 10874   |
| Dimensional Stability            | ≤0.05%  | EN ISO 23999   |
| Residual Indentation             | Norm: ≤0.10mm, 0.03mm   | EN ISO 24343-1 |
| Castor Chair                     | No Damage   | EN ISO 4918    |
| Light Fastness                   | ≥6  | EN ISO 105-BO2 |
| Light Reflectance Values         | 100 28160-45      190 28890-16      530 28282-27  |                |
| Slip Resistance                  | P2, R9  | AS/NZ 4586     |
| Residential Warranty*            | 25 Year Moduleo Residential Warranty  |                |
| Commercial Warranty <sup>†</sup> | 10 Years available upon request   |                |
| Reaction to Fire                 | CRF 6.4 kW/m <sup>2</sup><br>Smoke Value 130% Min   | EN ISO 9239    |
| Recommended Adhesive             | Refer to the Moduleo™ installation guidelines available at <a href="http://www.moduleo.com.au">www.moduleo.com.au</a> |                |

## SUSTAINABILITY SPECIFICATIONS

Indoor Air Quality | Green Building Council compliant for VOC emission rate limits



As part of the Mohawk Industries Inc. family, Godfrey Hirst has access to products and resources, including the high quality Moduleo™ product offering from the IVC Group.

Manufactured under a quality and environmental system as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances.

As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Moduleo™

floors must be installed in accordance with the relevant Australian Standards and in conjunction with the Moduleo™ Installation Instructions.

\*This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please

refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from [www.moduleo.com.au](http://www.moduleo.com.au).

<sup>†</sup>Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.

[www.moduleo.com.au](http://www.moduleo.com.au)